



SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD
(HCS) 29 CFR 1910.1200

Page 1 of 4
Revision Date 8/26/2015
Supersedes Date 7/30/2015

SECTION 1. IDENTIFICATION

Product identifier: JAX Chain Drive Pin & Bushing Lube (Trigger Spray)
Part number: 102TS-007
Identified uses: Lubricant where there is no possibility of contact with food
Uses advised against: Not for use where there is the possibility of contact with food. Other uses advised against may be specified elsewhere in this SDS.
Supplier: Pressure-Lube Inc. JAX
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051 USA
Email contact: info@jax.com
Non-emergency contact: Phone: 262-781-7660 Fax: 262-781-3906
Emergency telephone: INFOTRAC:
North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926
International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: Flammable Liquid Cat. 3; Aspiration Toxicity Cat. 1

Label elements

Pictograms:



Signal word: Danger

Hazard statements: Flammable liquid and vapor. May be fatal if swallowed and enters airways.

Precautionary statements: Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. Keep container tightly closed. Ground/ Bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF SWALLOWED: Immediately call a poison center/ doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. In case of fire: Use for extinction: CO2, powder or water spray. Store locked up. Store in a well-ventilated place. Keep cool. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Hazards not otherwise classified: Not applicable.

Additional information: Not applicable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Chemical name	%	CAS #	Impurities
	Naphtha (petroleum), hydrotreated heavy*	10-25	64742-48-9	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation persists, consult a physician.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

Ingestion: If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed: May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special See First aid measures (above).

treatment available:**General information:** No further relevant information available.**SECTION 5. FIRE-FIGHTING MEASURES****Suitable extinguishing media:** Carbon dioxide (CO₂), dry chemical or water spray. Fight larger fires with water spray or alcohol resistant foam.**Unsuitable extinguishing media:** Do not use direct stream of water.**Specific hazards:** Flammable liquid and vapor. Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.**Advice for firefighters:** Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined space or as otherwise needed.**SECTION 6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.**Environmental precautions:** Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.**Methods for containment and cleaning up**
Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.
Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.**SECTION 7. HANDLING AND STORAGE****Precautions for safe handling:** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.**Conditions for safe storage, including any incompatibilities:** Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

<u>Workplace exposure limits:</u>	<u>Chemical name</u>	<u>Exposure limit and source</u>
	Naphtha (petroleum), hydrotreated heavy*	Not available

Exposure controls**Engineering controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective occupational exposure limits.**Ventilation:** Use in a well-ventilated area. See Engineering Controls.**Personal hygiene:** Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.**Eye protection:** Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.**Hand protection:** Any lined non-permeable rubber gloves.**Respiratory protection:** Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance / odor:	Tacky, straw-colored lube oil with little or no odor	Upper flammability limit:	Not available
		Lower flammability limit:	Not available
Physical state:	Liquid	Vapor pressure:	Nil
Odor threshold:	Not available	Vapor density:	Not available
pH:	Not available		

Melting / freezing point:	Not available	Relative density:	0.84 (typical)
Initial boiling point and boiling range:	Not available	Solubility in water:	Nil
Flash point:	134°F (57°C), ASTM D 56	Partition coefficient (n-octanol/water):	Not available
Evaporation rate:	Nil	Autoignition temperature:	Not available
Flammability (solid, gas):	Not applicable	Decomposition temperature:	Not available
		Viscosity:	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Not reactive under normal conditions.
Chemical stability:	Stable under recommended conditions.
Possibility of hazardous reactions:	Hazardous reactions are not expected to occur.
Conditions and materials to avoid:	Avoid heat, sparks, open flames and strong oxidizing agents. Avoid prolonged storage at elevated temperatures.
Hazardous decomposition products:	Carbon monoxide, carbon dioxide, sulfur oxides, nitrogen oxides, phosphates, smoke and irritating vapors as products of incomplete combustion.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Eye contact:	No known significant effects or critical hazards.
Skin contact:	No known significant effects or critical hazards.
Inhalation:	May be fatal if swallowed and enters airways.
Ingestion:	May be fatal if swallowed and enters airways.

Component information:	Components	LD₅₀	LC₅₀
	Naphtha (petroleum), hydrotreated heavy*	>5000 mg/kg (oral, rat)	Not available

Information on physical, chemical and toxicological effects

Symptoms:	Please see Section 4 of this SDS for symptoms.
------------------	------------------------------------------------

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects:	May be fatal if swallowed and enters airways.
Carcinogenicity:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Numerical measures of toxicity:	Not determined
----------------------------------------	----------------

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Not available	
Component information:	Components	L(E)C₅₀
	Naphtha (petroleum), hydrotreated heavy*	Not available
Persistence and degradability:	Not determined	
Bioaccumulative potential:	Not determined	
Mobility in soil:	Not available	
Other adverse effects:	Not determined	

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods:	Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Consult national or regional authorities for proper disposal and reporting procedures.
---------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	UN Number:	Hazard Class:	Packing Group:	Remarks:
<u>U.S. D.O.T.</u>	Petroleum distillates, n.o.s.	UN1268	3	III	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
<u>ADR/RID</u>	Petroleum distillates, n.o.s.	UN1268	3	III	None
<u>IMDG</u>	Petroleum distillates, n.o.s.	UN1268	3	III	None
<u>IATA</u>	Petroleum distillates, n.o.s.	UN1268	3	III	None

SECTION 15. REGULATORY INFORMATION**U.S. Federal Regulations**

SARA Section 302 Extremely Hazardous Substances: This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: None

SARA Section 304 CERCLA Hazardous Substances: Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA: None

SARA Section 313 Toxic Chemicals: This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: None

TSCA Inventory: All components of this material are on the U.S. TSCA Inventory.

U.S. State Regulations

California Proposition 65 Status: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California Proposition 65 Listed Components: Ethyl acrylate

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the information required by those regulations.

Japan MITI: Not available

Australia: Not available

Switzerland: Not available

SECTION 16. OTHER INFORMATION

Sections Revised: New SDS format

Revision Date: 8/26/2015

The information and recommendations contained herein are, to the best of Pressure-Lube Inc. JAX's knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. JAX makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. JAX shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc. JAX's interpretation of the available data.

*** END OF SDS ***