



SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD
(HCS) 29 CFR 1910.1200

Page 1 of 5

Revision Date 11/7/2016

Supersedes Date 7/30/2015

SECTION 1. IDENTIFICATION

Product identifier: JAX Halo-Guard® FG-2

Part number: HLG02; HLG02N

Identified uses: Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

Supplier: JAX INC.
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency contact: Phone: 262-781-8850 Fax: 262-781-3906

Emergency telephone: INFOTRAC:
North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926
International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: Eye Irritation Cat. 2; Skin Sensitization Cat. 1

Label elements

Pictograms:



Signal word: Warning

Hazard statements: May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements: Avoid breathing fume/ mist/ vapors/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, or if skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Hazards not otherwise classified: Harmful to aquatic life with long lasting effects.

Additional information: Not applicable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Composition:</u>	<u>Chemical name</u>	<u>%</u>	<u>CAS #</u>	<u>Impurities</u>
	Distillates (petroleum), solvent-refined heavy paraffinic*	10-<20	64741-88-4	None
	Calcium carbonate (dust)	10-<20	471-34-1	None
	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	1-<5	148520-84-7	None
	Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts	1-<5	156105-31-6	None
	Calcium dodecylbenzene sulphonate	1-<5	26264-06-2	None
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	1-<5	68411-46-1	None
	Sulfonic acids, petroleum, calcium salts	1-<5	61789-86-4	None
	Zinc oxide	1-<2.5	1314-13-2	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for 15 minutes. If irritation persists, consult a physician.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

Ingestion: If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: If exposed to excessive levels of material in the air, move the exposed person to fresh air. Seek medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed: May cause an allergic skin reaction. Causes serious eye irritation.

Indication of any immediate medical attention and special treatment available: See First aid measures (above).

General information: No further relevant information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide (CO₂), dry chemical or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media: Do not use direct stream of water.

Specific hazards: Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool. Burning produces noxious and toxic fumes.

Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed. Prevent fire-extinguishing water from contaminating surface water or the groundwater system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Methods for containment and cleaning up

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Keep container closed when not in use.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry place in tightly sealed containers. Store in out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from strong acids, strong bases, and strong oxidizing agents. Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Workplace exposure limits:</u>	<u>Chemical name</u>	<u>Exposure limit and source</u>
	Distillates (petroleum), solvent-refined heavy paraffinic*	5 mg/m ³ (oil mist), OSHA
	Calcium carbonate (dust)	TWA (respirable) = 5 mg/m ³ (NIOSH REL)
	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy	Not available
	Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts	Not available
	Calcium dodecylbenzene sulphonate	Not available
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Not available
	Sulfonic acids, petroleum, calcium salts	Not available
	Zinc oxide	2 mg/m ³ (TWA), ACGIH 10 mg/m ³ (STEL), ACGIH

Exposure controls

Engineering controls:

may be required to maintain air concentrations below recommended exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Appearance / odor:</u>	White semi-solid with mild petroleum odor	<u>Upper flammability limit:</u>	Not determined
		<u>Lower flammability limit:</u>	Not determined
<u>Physical state:</u>	Semi-solid	<u>Vapor pressure:</u>	Not available
<u>Odor threshold:</u>	Not available	<u>Vapor density:</u>	Not available
<u>pH:</u>	Not available		
<u>Melting / freezing point:</u>	Not available	<u>Relative density:</u>	0.95-1.05
<u>Initial boiling point and boiling range:</u>	Not available	<u>Solubility in water:</u>	Negligible
<u>Flash point:</u>	350°F (177°C), ASTM D 92	<u>Partition coefficient (n-octanol/water):</u>	Not available
<u>Evaporation rate:</u>	Not available	<u>Autoignition temperature:</u>	Not available
<u>Flammability (solid, gas):</u>	Not applicable	<u>Decomposition temperature:</u>	Not available
		<u>Viscosity:</u>	Not available

SECTION 10. STABILITY AND REACTIVITY

<u>Reactivity:</u>	Not reactive under normal conditions.
<u>Chemical stability:</u>	Stable under recommended conditions.
<u>Possibility of hazardous reactions:</u>	Hazardous reactions are not expected to occur.
<u>Conditions and materials to avoid:</u>	Keep away from heat, sparks, open flames and other sources of ignition. Keep out of direct sunlight. Avoid strong acids, strong bases, and strong oxidizing agents.
<u>Hazardous decomposition products:</u>	Carbon oxides, metal oxides, nitrogen oxides (NOx), and sulfur oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

<u>Eye contact:</u>	Causes serious eye irritation.
<u>Skin contact:</u>	May cause an allergic skin reaction.
<u>Inhalation:</u>	No known significant effects or critical hazards.
<u>Ingestion:</u>	No known significant effects or critical hazards.

<u>Component information:</u>	<u>Components</u>	<u>LD₅₀</u>	<u>LC₅₀</u>
	Distillates (petroleum), solvent-refined heavy paraffinic*	Not available	Not available
	Calcium carbonate (dust)	Not available	Not available
	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy	Not available	Not available
	Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts	Not available	Not available
	Calcium dodecylbenzene sulphonate	>4199 mg/kg (dermal, rabbit)	Not available
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	>2000 mg/kg (oral, rat)	Not available

Sulfonic acids, petroleum, calcium salts	>5000 mg/kg (oral, rat)	Not available
Zinc oxide	5000 mg/kg (oral, rat)	Not available

Information on physical, chemical and toxicological effects

Symptoms: See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects: May cause an allergic skin reaction. Causes serious eye irritation.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Numerical measures of toxicity: Not determined

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Component information:	Components	<u>LEIC₅₀</u>
	Distillates (petroleum), solvent-refined heavy paraffinic*	Not available
	Calcium carbonate (dust)	Not available
	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy	Not available
	Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts	Not available
	Calcium dodecylbenzene sulphonate	2.5 mg/l/48h [Daphnia magna (Water flea)]
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	>71 mg/l/96h [Danio rerio (zebra fish)]
	Sulfonic acids, petroleum, calcium salts	>100 mg/l/48h [Daphnia magna (Water flea)]
	Zinc oxide	1.1 mg/l/96h [Oncorhynchus mykiss (rainbow trout)]

Persistence and degradability: Not determined

Bioaccumulative potential: Not determined

Mobility in soil: Not available

Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	<u>Proper Shipping Name:</u>	<u>UN Number:</u>	<u>Hazard Class:</u>	<u>Packing Group:</u>	<u>Remarks:</u>
<u>U.S. D.O.T.</u>	Not regulated	None	None	None	None
<u>ADR/RID</u>	Not regulated	None	None	None	None
<u>IMDG</u>	Not regulated	None	None	None	None
<u>IATA</u>	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION**U.S. Federal Regulations**

SARA Section 302 Extremely Hazardous Substances: This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:
None

SARA Section 304 CERCLA Hazardous: Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA:

Substances: None

SARA Section 313 Toxic Chemicals: This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

Zinc oxide, CAS # 1314-13-2, present at <2.5%

TSCA Inventory: All components of this material are on the U.S. TSCA Inventory.

U.S. State Regulations

California Proposition 65 Status: This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California Proposition 65 Listed Components: None

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the information required by those regulations.

Japan MITI: Not available

Australia: Not available

Switzerland: Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Section 3

Revision Date: 11/7/2016

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.

*** END OF SDS ***