

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD

(HCS) 29 CFR 1910.1200

SECTION 1. IDENTIFICATION

Product identifier:	JAX Magna-Kote® 412
Part number:	41200
Identified uses:	Lubricant where there is no possibility of contact with food
Uses advised against:	Not for use where there is the possibility of contact with food. Other uses advised against may be specified elsewhere in this SDS.

Supplier:	JAX INC					
	W134 N5373 Campbell Drive					
	Menomonee Falls, WI 53051 USA					
Email contact:	info@jax.com					
Non-emergency	Phone: 262-781-8850 Fax: 262-781-39	06				
<u>contact:</u>						
Emergency telephone:	INFOTRAC:					
	North America 1-800-535-5053	Australia 1-300-366-961	Germany 0800-181-2926			
	International 011-1-352-323-3500 (collect)	China 400-120-0761				

SECTION 2. HAZARD(S) IDENTIFICATION

Danger

Classification:

Flammable Liquid Cat. 3; Skin Irritation Cat. 2; Eye Irritation Cat. 2A; STOT SE 3 (Central nervous system); Aspiration Toxicity Cat. 1

Label elements **Pictograms:**

Signal word:



Hazard statements: Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Precautionary

Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. Keep container tightly closed. Ground/ Bond statements: container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ eye protection/ face protection. Wash skin thoroughly after handling. Avoid breathing fume/ mist/ vapors/ spray. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a poison center/ doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. In case of fire: Use carbon dioxide (CO2), dry sand, dry chemical or alcohol-resistant foam for extinction. Store locked up in a well-ventilated place. Keep cool. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Hazards not otherwise Not applicable. classified:

Additional information: Not applicable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS						
Composition:	Chemical name	<u>%</u>	CAS #	Impurities		
	Naphtha (petroleum), hydrotreated heavy*	70-98	64742-48-9	None		
	Stoddard solvent*	<2	8052-41-3	None		
	1,2,4-trimethylbenzene	<0.1	95-63-6	None		

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact:

Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation persists, consult a physican.

JAX Magna-Kote® 412		Page 2 of 5 Revision Date Supersedes Date	8/14/2018 7/12/2018
Skin contact:	Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clear reuse and discard oil-soaked shoes. If irritation persists, consult a physician.	n contaminated clothi	ng before
Ingestion:	If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to Never give anything by mouth to an unconscious person. Consult a physician.	drink and seek medic	al attention.
Inhalation:	Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respi immediately.	ration. Get medical at	tention
<u>Most important</u> symptoms and effects, both acute and delayed:	Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May airways.	be fatal if swallowed	and enters
Indication of any immediate medical attention and special treatment available:	See First aid measures (above).		
General information:	No further relevant information available.		
SECTION 5. FIRE-FIGHTIN	IG MEASURES		
Suitable extinguishing media:	Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use dire used to keep fire-exposed containers cool.	ect stream of water. W	/ater may be
Unsuitable extinguishing media:	Do not use direct stream of water.		
Specific hazards:	Flammable liquid and vapor. Pressure build-up due to heat exposure may cause containers t keep containers cool.	o rupture. Use water	spray to
Advice for firefighters:	Firefighters should wear full protective gear, including helmet. Use supplied-air breathing ec space or as otherwise needed.	uipment for enclosed	l or confined
SECTION 6. ACCIDENTAL	RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all away from ignition sources. Wear protective equipment. Keep unprotected persons away.	applicable regulation	s. Keep
Environmental precautions:	Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far al disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or		
<u>Methods for</u> <u>containment and</u> <u>cleaning up</u>	Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking suitable absorbent material to the spill area. Recover by pumping or with suitable absorbent national and/or local regulations relating to waste disposal. Water spill: Stop leak if you can do so without risk. Confine the spill immediately with boom skimming or with suitable absorbents. Seek the advice of a specialist before using dispersant	ts. Dispose of in accor	dance with
SECTION 7. HANDLING AND) STORAGE		
Precautions for safe handling:	Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workpla ignition - Do not smoke. Protect against electrostatic charges.	ace. Keep away from s	sources of
<u>Conditions for safe</u> <u>storage, including any</u> incompatibilities:	Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store pilot lights, static electricity, or other sources of ignition. Do not store where temperature maway from oxidizing agents. Rotate stock.		•
SECTION 8. EXPOSURE C	ONTROLS / PERSONAL PROTECTION		
Workplace exposure	Chemical name Exposure limit and source		

	·······	
Workplace exposure	Chemical name	Exposure limit and source
limits:	Naphtha (petroleum), hydrotreated heavy*	Not available
	Stoddard solvent*	Not available
	1,2,4-trimethylbenzene	Long-term value: 125 mg/m ³ , 25 ppm
Exposure controls		
Engineering controls:	Provide exhaust ventilation or other engineering contro occupational exposure limits.	Is to keep the airborne concentration of vapors below their respective
Ventilation:	Use in a well-ventilated area. See Engineering Controls.	
Personal hygiene:	Wash skin thoroughly after contact, before breaks and	meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / odor:	Dark gray fluid, very low viscosity, slight mineral	Upper flammability limit:	Not available
	spirits odor	Lower flammability limit:	Not available
Physical state:	Liquid	Vapor pressure:	Not available
Odor threshold:	Not available	Vapor density:	A
<u>рН:</u>	Not available		Not available
Melting / freezing point	<u>::</u> Not available	Relative density:	0.77 (typical)
Initial boiling point	Not available		
and boiling range:		Solubility in water:	Insoluble
Flash point:	108°F (42°C), ASTM D 56	Partition coefficient	Not available
		<u>(n-octanol/water):</u>	
Evaporation rate:	Not available	Autoignition temperature:	Not available
Flammability (solid, gas):	Not applicable	Decomposition temperature:	Not available
- 101111001114 (30110, <u>503)</u> .		Viscosity:	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Not reactive under normal conditions.
Chemical stability:	Stable under recommended conditions.
<u>Possibility of</u> hazardous reactions:	Hazardous reactions are not expected to occur.
Conditions and materials to avoid:	Keep away from heat, sparks, open flames, and other sources of ignition. Keep out of direct sunlight. Avoid strong oxidizers, strong alkalis, and strong acids.
<u>Hazardous</u> decomposition products:	Carbon monoxide, carbon dioxide, oxides of sulfur, smoke and irritating vapors as products of incomplete combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact:	Causes serious eye irritation.					
Skin contact:	Causes skin irritation.	Causes skin irritation.				
Inhalation:	May cause drowsiness or dizziness. May be fatal if	May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.				
Ingestion:	May cause drowsiness or dizziness. May be fatal if	f swallowed and enters airways.				
<u>Component</u>	<u>Components</u>	LD ₅₀	<u>LC₅₀</u>			
information:	Naphtha (petroleum), hydrotreated heavy*	>5000 mg/kg (oral, rat)	Not available			
	Stoddard solvent*	Not available	Not available			
	1,2,4-trimethylbenzene	5000 mg/kg (oral, rat)	Not available			
Information on phys	ical, chemical and toxicological effects					
Symptoms:	See Section 4 of this SDS for symptoms.					
Delayed and immedi	ate effects, and chronic effects, from short and long-to	erms exposure				
Effects:	Causes skin irritation. Causes serious eye irritation airways.	Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.				
Carcinogenicity:	No companent of this product present at lovels gr	easter than ar aqual to 0.10/ is iden	tified as a known or anticipated			

- **Carcinogenicity:** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- Numerical measures of Not determined

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Not available	
<u>Component</u>	Components	<u>L(E)C₅₀</u>
information:	Naphtha (petroleum), hydrotreated heavy* Stoddard solvent*	Not available Not available
	1,2,4-trimethylbenzene	Not available
Persistence and degradability:	Not determined	
<u>Bioaccumulative</u> potential:	Not determined	
Mobility in soil:	Not available	
Other adverse effects:	Not determined	

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatmentDisposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.methods:Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	UN Number:	Hazard <u>Class:</u>	Packing <u>Group:</u>	Remarks:
<u>U.S. D.O.T.</u>	Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)	UN1993	3	III	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)	UN1993	3	III	None
IMDG	Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)	UN1993	3	III	None
<u>IATA</u>	Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)	UN1993	3	III	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA Section 302 Extremely Hazardous Substances:	This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: None
SARA Section 304 CERCLA Hazardous Substances:	Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA: Naphthalene (CAS# 91-20-3) 100 lbs. (45.4 kg)* *Calculated RQ exceeds reasonably attainable upper limit.
SARA Section 313 Toxic Chemicals:	This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: None
TSCA Inventory:	All components are either listed or exempted from listing on the TSCA Inventory.
U.S. State Regulations	
California Proposition 65 Status:	This product contains chemical(s) known to the State of California to cancer, birth defects, or other reproductive harm.
California Proposition 65 Listed Components:	Ethylbenzene; Naphthalene

International Regulations

Canada:

This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

JAX Magna-Kote [®] 412		Page 5 of 5 Revision Date Supersedes Date	8/14/2018 7/12/2018
	information required by those regulations.		
Japan MITI: Australia: Switzerland:	Not available Not available Not available		
SECTION 16. OTHER INF	ORMATION		
Sections Revised:	Sections 3, 8, 11, 12 and 15		
Revision Date:	8/14/2018		

The information and recommendations contained herein are, to the best of JAX INC's knowledge and belief, accurate and reliable as of the date issued. JAX INC makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC's interpretation of the available data.

*** END OF SDS ***