

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 4

7/12/2018 **Revision Date Supersedes Date** 3/28/2018

SECTION 1. IDENTIFICATION

Product identifier: JAX Unitran® Fluid HD - Red

460HD Part number:

Identified uses: Hydraulic/transmission fluid

Uses advised against: Any use not specified above, or any use specified against elsewhere in this SDS.

JAX INC Supplier:

> W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency Phone: 262-781-8850 Fax: 262-781-3906

contact:

INFOTRAC: Emergency telephone:

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: Skin Sensitization Cat. 1

Label elements

Pictograms:



Warning Signal word:

Hazard statements: May cause allergic skin reaction.

Precautionary statements:

Avoid breathing fume/ mist/ vapors/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse. Dispose of contents/ container in accordance with local/ regional/

national/international regulations.

Hazards not otherwise Not applicable.

classified:

Additional information: Not applicable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	<u>Chemical name</u>	<u>%</u>	CAS#	<u>Impurities</u>
	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*	70-90	72623-86-0	None
	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	1-5	4259-15-8	None
	Aryl phosphite	<1	101-02-0	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

Most important

Causes serious eye irritation. May cause allergic skin reaction.

symptoms and effects,

Page 2 of 4 JAX Unitran® Fluid HD - Red

Revision Date Supersedes Date

7/12/2018 3/28/2018

both acute and delayed:

Indication of any immediate medical attention and special treatment available:

See First aid measures (above).

General information:

No further relevant information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing

media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be

used to keep fire-exposed containers cool.

Unsuitable extinguishing media: Do not use direct stream of water.

Specific hazards:

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment

and emergency procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Methods for containment and

Environmental

precautions:

cleaning up

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe

handling:

limits:

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure

Chemical name

Exposure limit and source Lubricating oils (petroleum), C15-30, hydrotreated 5 mg/m³ (oil mist), OSHA

neutral oil-based*

Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) Not available Aryl phosphite Not available

Exposure controls

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

JAX Unitran® Fluid HD - Red

Page 3 of 4

Not available

Not available

7/12/2018 **Revision Date** 3/28/2018 **Supersedes Date**

Red-colored lube oil with little or no odor **Upper flammability limit:** Not available Appearance / odor:

> Lower flammability limit: Not available

Liquid **Physical state:** Vapor pressure: Nil

Odor threshold: Not available Vapor density:

Not available pH:

Melting / freezing point: Not available Relative density: 0.87 (typical)

Initial boiling point Not available and boiling range:

Solubility in water: Nil Flash point: 419°F (215°C), ASTM D 92 Not available

Partition coefficient (n-octanol/water):

Evaporation rate: Nil **Autoignition temperature:** Not available

Decomposition temperature: Not available

Flammability (solid, gas): Not applicable Viscosity: Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions. Chemical stability: Stable under recommended conditions.

Possibility of Hazardous reactions are not expected to occur.

hazardous reactions:

Conditions and Avoid heat, sparks, open flames, acids and oxidizing materials.

materials to avoid:

Hazardous Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of phosphorus, oxides of calcium, oxides of zinc, aldehydes,

decomposition hydrogen sulfide, alkyl mercaptans, smoke and irritating vapors as products of incomplete combustion.

products:

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

No known significant effects or critical hazards. Eye contact:

Skin contact: May cause allergic skin reaction.

Inhalation: No known significant effects or critical hazards. Ingestion: No known significant effects or critical hazards.

Components <u>LC</u>50 LD₅₀ Component

information: Lubricating oils (petroleum), C15-30, hydrotreated >5000 mg/kg (oral, rat)

neutral oil-based*

Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) Not available Not available Aryl phosphite Not available Not available

Information on physical, chemical and toxicological effects

Symptoms: See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects: May cause allergic skin reaction.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated

carcinogen by NTP.

Numerical measures of Not determined

toxicity:

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: No known significant effects.

L(E)C₅₀ Component Components

information: Lubricating oils (petroleum), C15-30, hydrotreated

neutral oil-based*

Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) Not available

0.94 mg/l/48h (Daphnia magna) Aryl phosphite

Not available

JAX Unitran® Fluid HD - Red
Page 4 of 4
Revision Date

Revision Date
Supersedes Date

7/12/2018 3/28/2018

Persistence and

Not determined

degradability:

<u>Bioaccumulative</u>

Not determined

potential:

Mobility in soil: Not available

Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

<u>Waste treatment</u> Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

methods: Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	UN Number:	Class:	Group:	Remarks:
<u>U.S. D.O.T.</u>	Not regulated	None	None	None	None
ADR/RID	Not regulated	None	None	None	None
<u>IMDG</u>	Not regulated	None	None	None	None
<u>IATA</u>	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA Section 302 This pro

This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

Extremely Hazardous

Substances:

lone

SARA Section 304 CERCLA Hazardous Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to

CERCLA Hazardous reporting to the National Response Center under CERCLA:

Substances: None

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

Chemicals:

Category: Zinc compounds 1-2%

TSCA Inventory: All components are either listed or exempted from listing on the TSCA Inventory.

U.S. State Regulations

California Proposition

65 Status:

This product contains chemical(s) known to the State of California to cancer, birth defects, or other reproductive harm.

California

Ethylbenzene

Proposition 65
Listed Components:

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

information required by those regulations.

Japan MITI:Not availableAustralia:Not availableSwitzerland:Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Section 15
Revision Date: 7/12/2018

The information and recommendations contained herein are, to the best of JAX INC's knowledge and belief, accurate and reliable as of the date issued. JAX INC makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC's interpretation of the available data.