

Version number 1

Revision: 30.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation: Lubricant where there is no possibility of contact with food.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

JAX INC. W134 N5373 CAMPBELL DRIVE MENOMONEE FALLS, WI 53051 USA Tel: +01-262-781-8850 Fax: +01-262-781-3906

Further information obtainable from:

REACH Only Representative B-Lands Consulting WTC, 5 Place Robert Schuman, BP 1516 38025 Grenoble, FRANCE Tel: +33 476 295 869 Fax: +33 476 295 870 services@reachteam.eu www.reachteam.eu

1.4 Emergency telephone number

UK - National Poisons Emergency: +44 870 600 6266 (24h - health professionals only). Ireland - National Poisons Information Centre: +353 1 8379964.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

This product is not classified as hazardous according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008: Not applicable.

Hazard pictograms: Not applicable.

Signal word: Not applicable.

Hazard statements: Not applicable.

Additional information: Safety data sheet available on request.

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components:				
CAS: 68955-53-3	Amines, C12-14-tert-alkyl		<2.5%	
EINECS: 273-279-1		Aquatic Chronic 2, H411; Eye Irrit. 2, H319		

according to 1907/2006/EC, Article 31

Printing date 30.08.2016

Version number 1

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

Non-hazardous components:	
CAS: 68037-01-4 Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, NLP: 500-183-1 hydrogenated (Polyalphaolefin).	50-100%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: No special measures required.

After inhalation: Supply fresh air. Consult a doctor if symptoms persist.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Remove contact lenses, if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow product to reach sewage system or any water course. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016

Version number 1

Revision: 30.08.2016

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: Store in a cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions: None.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection: Not required.

Protection of hands:



Protective gloves

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Eye protection:



Safety glasses with side-shields (EN 166).

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:	
Form:	Liquid.
Colour:	Amber coloured.
Odour:	Sulfurous.
Odour threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.
Flash point:	229 °C (ASTM D 92)

according to 1907/2006/EC, Article 31

Printing date 30.08.2016

Version number 1

Revision: 30.08.2016

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits: Lower: Upper:	Not determined. Not determined.	
Oxidizing properties	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	0.86-0.89 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with water:	Not determined.	
Partition coefficient (n-octanol/water): Not determined.		
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
9.2 Other information	No further relevant information available.	
SECTION 10: Stability and reactivi	ity	

SECTION 10: Stability and reactivity

10.1 Reactivity No data available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Keep away from heat and direct sunlight.

10.5 Incompatible materials Avoid strong oxidants, strong alkalis and strong acids.

10.6 Hazardous decomposition products Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Primary irritant effect: on the skin: No irritant effect. on the eye: No irritating effect known.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016

Version number 1

Revision: 30.08.2016

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Do not allow product to reach sewage system.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN Number ADR, ADN, IMDG, IATA	Not applicable.
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Not applicable.
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Not applicable.
14.4 Packing group ADR, IMDG, IATA	Not applicable.
14.5 Environmental hazards Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016

Version number 1

Revision: 30.08.2016

Trade name: JAX Synax EP Gear Oil 150, 220, 320, 460, 680

Relevant phrases

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)