# JAX

# **Safety Data Sheet**

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Application of the substance / the preparation:

Lubricant where there is no possibility of contact with food.

#### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

JAX INC.

W134 N5373 CAMPBELL DRIVE MENOMONEE FALLS, WI 53051 USA

Tel: +01-262-781-8850 Fax: +01-262-781-3906

#### Further information obtainable from:

REACH Only Representative B-Lands Consulting WTC, 5 Place Robert Schuman, BP 1516 38025 Grenoble, FRANCE

Tel: +33 476 295 869 Fax: +33 476 295 870

Email: services@reachteam.eu Web: www.reachteam.eu

#### 1.4 Emergency telephone number:

UK - National Poisons Emergency: +44 870 600 6266 (24h - health professionals only). Ireland - National Poisons Information Centre: +353 1 8379964.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

This product is not classified as hazardous according to Regulation (EC) No 1272/2008.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008: Not applicable.

Hazard pictograms: Not applicable.

Signal word: Not applicable.

Hazard statements: Not applicable.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

| Hazardous components:                |   |        |
|--------------------------------------|---|--------|
| CAS: 68955-53-3<br>EINECS: 273-279-1 | Amines, C12-14-tert-alkyl                               | <0.25% |
|                                      | Acute Tox. 3, H311; Acute Tox. 2, H330; STOT RE 2, H373 |        |

Additional information: For the wording of the listed risk phrases refer to section 16.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

**Trade name:** JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General information: No special measures required.

**After inhalation:** Move patient to fresh air, if symptoms persist consult a doctor. **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

#### After eye contact:

Remove contact lenses, if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet.

#### 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

#### 5.3 Advice for firefighters

Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions** Do not allow product to reach sewage system or any water course.

#### 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:** No special measures required.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements to be met by storerooms and receptacles:

Store in a cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility: Store away from oxidizing agents.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

Trade name: JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

Further information about storage conditions: None.

7.3 Specific end use(s): No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

#### Personal protective equipment

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection: Not required.

Protection of hands:



Protective gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

#### Eye protection:



Safety glasses with side-shields (EN 166).

Body protection: Protective work clothing.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

#### **General Information**

Appearance:

Flash point:

Form: Liquid. Colour: Amber. Odour: Light

Odour threshold: Not determined. pH-value: Not determined. Melting point/Melting range: Not determined. Boiling point/Boiling range: Not determined. 210 °C (ASTM D 92)

Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. **Decomposition temperature:** Not determined.

Danger of explosion: Product does not present an explosion hazard.

**Explosion limits:** 

Lower: Not determined.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

Trade name: JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

Upper: Not determined.

Oxidizing properties Not determined.

Vapour pressure: Not determined.

Density: Not determined.

Relative density at 20 °C 0.86-0.89 g/cm³

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

water: Not determined.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

**9.2 Other information**No further relevant information available.

#### **SECTION 10: Stability and reactivity**

10.1 Reactivity No data available.

#### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid Keep away from heat and direct sunlight.
- 10.5 Incompatible materials Avoid strong oxidants, strong alkalis and strong acids.
- **10.6 Hazardous decomposition products** Carbon monoxide and carbon dioxide.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

#### **Primary irritant effect:**

on the skin: No irritant effect known. on the eye: No irritating effect known.

**Sensitization:** No sensitizing effects known.

#### Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

**Trade name:** JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

#### **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

**Recommendation:** Do not allow product to reach sewage system.

**Uncleaned packaging** 

**Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

14.1 UN Number

ADR, ADN, IMDG, IATA Not applicable.

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Not applicable.

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Not applicable.

14.4 Packing group

ADR, IMDG, IATA Not applicable.

14.5 Environmental hazards

Marine pollutant: No

**14.6 Special precautions for user**Not applicable.

14.7 Transport in bulk according to Annex II

of MARPOL 73/78 and the IBC Code Not applicable.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### **Relevant phrases**

H311 Toxic in contact with skin.

H330 Fatal if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

according to 1907/2006/EC, Article 31

Printing date 30.08.2016 Version number 1 Revision: 30.08.2016

Trade name: JAX Way-Tac Lubricant ISO 32, 46, 68, 100, 150 and 220

IMDG: International Maritime Code for Dangerous Goods

INDG: International Mantime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)